

SOLESBEE'S.COM  
+1(800) 419-8090



## TC1F-120 FRONT MULCHER

POWERED BY  CANGINI

### SOLESBEE'S TC1F-120 FRONT MULCHER

Powered by Cangini

The front mulcher is designed for brushwood clearance and maintaining public green areas. Adjustable support rollers and machine coupling allow for precise cutting mode selection. Equipped with a reinforced body and  $\pm 10^\circ$  self-levelling system, the front mulcher ensures accurate operation and efficient performance as it adjusts to the level of the ground as you drive your machine.

- ☒ Quality Material
- ☒ Availability
- ☒ 2 Year Warranty

#### VERTICAL TILT

Allows for better follow with the course of the ground, automatically controlled by gravity

#### REINFORCED BODY

Composed of double bottoms that provide high impact resistance, preventing deformation of the frame if excessive pressure is exerted on the ground.



#### SHAFT CONFIGURATION

The hammer shaft set-up is especially designed to withstand heavy works, such as cutting shrubs up to a diameter of 10cm.


#### GEAR MOTOR

Motor equipped with HPS seals capable of supporting back pressures of up to 145 psi





# SPECIFICATIONS



	MOD.	TC1F-120
A	IN	47
B	IN	55
C	IN	25
D	IN	20
E	IN	31
W/O COUPLER	LB	385.80
		DIRECT
MIN.	GAL/MIN	6
MAX.	GAL/MIN	24
MAX.	PSI	3626
MAX WITH HAMMERS	IN	1.6
MAX MECHANICAL	IN	-



W/O COUPLER



## TC1F-120 FRONT MULCHER POWERED BY CANGINI

## FEATURES

- Complete with hydraulic hoses L= 2000 mm and 3/4" (male/female) flat-face couplings
- Automatic self-leveling right and left tilt +/- 10° to better follow the course of the ground
- Composed of double bottoms that provide high impact resistance

## APPLICATIONS

- Ideal tool for both forest care and park and garden maintenance works



### STANDARD TECHNICAL FEATURES

- INTEGRATED VALVE UNIT**  
THROTTLE, PRESSURE RELIEF AND BYPASS VALVES.
- MECHANICAL SIDE-SHIFTING (L-R)**  
IT SHIFTS THE MULCHER ON BOTH SIDES WITH RESPECT TO THE MACHINE TRACK.
- REINFORCED BODY**  
DOUBLE REINFORCED BODY FOR A HIGHER RESISTANCE TO SHOCKS.
- SHAFT WITH HAMMERS**  
SUITABLE FOR THE CUTTING OF SHRUBS OR SIMILAR PLANTS.
- SHAFT WITH BLADES**  
SUITABLE FOR THE CUTTING OF GRASS OR SIMILAR VEGETATION.
- FLOATING SYSTEM**  
IT ENABLES THE MULCHER TO FOLLOW THE SOIL.
- SELF-LEVELLING OF THE HORIZONTAL PLANE OF ± 10°**
- GEAR MOTOR**  
MOTOR WITH REINFORCED SEAL, DIRECT DRAINAGE LINE LINKED TO THE TANK IS MANDATORY.

### OPTIONAL

- LATERAL HYDRAULIC SIDE-SHIFTING THANKS TO 2 HOSES TRANSLATION KIT**  
FIT FOR PARTICULARLY HARD AND CONTINUOUS WORKS. NEEDS THE DIRECT DRAINING PIPE TO THE TANK, DIRECTLY FROM THE CAB.
- PISTON ENGINE**  
FIT FOR PARTICULARLY HARD AND CONTINUOUS WORKS. NEEDS THE DIRECT DRAINING PIPE TO THE TANK, THE APPLICATION ON THE OPERATING MACHINE WILL BE CHECKED BEFORE ORDER CONFIRMATION.
- ARTICULATED LOADERS HITCH**
- ELECTRIC KIT**  
THE CONNECTOR TYPE YOU REQUIRE MUST BE INDICATED AT THE TIME OF ORDERING.



Solesbee's Equipment  
2640 Jason Industrial Pkwy,  
Winston, GA 30187

+1 (800) 419-8090  
sales@solesbees.com

@solesbeesequipment

